#### Backplane Systems Technology Pty Ltd

TEL 02 9457 6400 sales@backplane.com.au www.backplane.com.au

# 450i & 450 SERIES





- Generic keyboard (HID) device no additional drivers needed
- Factory configured to encode telephone or calculator format numeric keypads
- Output code table can be customised using the USB Configuration Utility (available for free download from www.storm-interface.com)
- 450i version includes an integrated power supply and provides colour and brightness control for keypad illumination (where fitted)
- 450i version features a piezo sounder for optional key press confirmation or status signal
- Simple connection via a USB Mini-B socket
- Compact, self contained form factor
   Compatible with most Storm 4, 12 and 16 key format keypads (including Storm 700, 720,1000, 2000, 3000, GFX and PLX product series)

# **USB 2.0 Keypad Encoder**

This self-contained device is ready to use.
It can be easily attached to the rear surface of most Storm keypads to provide connectivity and communication with USB compatible host systems. Factory configured for standard numeric data entry, this versatile device can also be user programmed to output alternative key codes; making the 450 Series Encoder the ideal keypad interface for most applications.

#### **Features**

- Direct connection to keypad via integral 0.1" pitch, square pin, female connector (included)
- Connection to host system via cable fitted with USB Mini-B male connector (supplied separately)
- Integral cable tie anchor points to secure USB cable

#### Compliance (designed to meet)

- EU RoHS
- EU Low Voltage Directive
- EMC: Emissions and Immunity: FCC part 15 class A
- EN55022, EN55024
- ESD: Up to +/- 15kV air discharge, +/- 7.5kV contact discharge
- WEEE Directive compliant

#### **Performance**

Operational temperature -20°C to +60°C -20°C to +70°C Storage temperature Humidity 10% to 90% non-condensing Vibration and shock ETSI 300 019 5M3 Insulation resistance 50Mohms (min) 500V a.c. (60 secs) Breakdown voltage Operating voltage 5V +/- 5% (USB) Operating current 20mA (excluding keypad illumination current)











### Encoder Part No.s

450i **4500-10** 450 **4500-00** 

## **Accessories Part No.s**

 USB cable fitted with 90° angled Mini-B male connector (to encoder) and USB-A male connector (to host system).

Optional encoder configuration software (free download)

4500-SW01

4500-01

is made to ensure details are correct at time of print specifications are subject to change without notice

by NIK Designed

Storm Interface products include technology protected by international patents and design registration. All rights reserved

Storm is a trademark
of Keymat Technology Ltd
torm Interface is a trading name
of Keymat Technology Ltd







FM 39602

