

NS-205AFC-T/FCS-T/FCS-60T

NS-206AFT-T

NSM-205AFC-T/FCS-T/FCS-60T

NSM-206AFT-T



NS(M)-205AF/NS(M)-206AF Series

LAN x4	Wide Temperature -30 ~ +75	DIN-Rail Mount	Wide Input Voltage +12 ~ +48	CE	FCC	RoHS	WEEE	For NS(M)-205AF 100Base-FX x1	For NS(M)-206AF 100Base-FX x2
--------	----------------------------	----------------	------------------------------	----	-----	------	------	-------------------------------	-------------------------------

Features ▶▶▶

- Provides 1 x 100-FX fiber port for NS-205AF/NSM-205AF series
- Provides 2 x 100-FX fiber ports for NS-206AF/NSM-206AF series
- Full duplex IEEE 802.3x and half duplex backpressure flow control
- Supports operating temperatures from -30 °C ~ +75 °C
- Automatic MDI/MDI-X crossover for plug-and-play
- Store-and-forward architecture
- Redundant dual +12 V_{DC} ~ +48 V_{DC} power inputs
- DIN-Rail Mounting

Introduction

The NS-206AF/NSM-206AF is a 4-port unmanaged Ethernet with 2 fiber ports switch. Using fiber optics, you can prevent noise from interfering with your system and supports high-speed (100 Mbps) and high-distance (up to 60 km) transmissions.

The NS-205AF/NSM-205AF/NS-206AF/NSM-206AF provides a wide +12 V_{DC} ~ +48 V_{DC} power range to fit all the common power standards found in industrial automation, without external power converters. The wide power input lowers installation and maintenance costs.

Comparison Table of Fiber Switch

Mode Name	NS-205F NS-206F	NSM-205F NSM-206F	NS-205AF NS-206AF	NSM-205AF NSM-206AF
PoE	-			
Input Voltage Range	+10 V _{DC} ~ +30 V _{DC}		+12 V _{DC} ~ +48 V _{DC}	
Operating Temperature	0 °C ~ +70 °C		-30 °C ~ +75 °C	
Casing	Plastic	Metal (IP20)	Plastic	Metal (IP30)
Installation	DIN-Rail Mounting	DIN-Rail Mounting or Wall Mounting	DIN-Rail Mounting	
Dimensions (W x L x H) (Unit: mm)	64 x 98 x 110	73 x 102 x 110	31 x 127 x 157	25 x 133 x 168

Specifications

Models	NS-205AF Series	NS-206AF Series	NSM-205AF Series	NSM-206AF Series
Technology				
Standards	IEEE 802.3, 802.3u, 802.3x			
Processing Type	Store & forward; wire speed switching			
MAC Addresses	1024			
Memory Bandwidth	2.0 Gbps			
Frame Buffer Memory	512 Kbit			
Flow Control	IEEE 802.3x flow control			
Ethernet Interface				
RJ-45 Ports	10/100 Base-T(X) auto negotiation speed, F/H duplex mode, and auto MDI/MDI-X connection			
LED Indicators	Power, Link/Act, 10/100M			
Ethernet Isolation	1500 V _{rms} 1 minute			
+/-4 kV ESD Protection	Yes			
Fiber Interface (100 Base-FX; SC/ST type)				
Multi-Mode	NS-205AFT-T NS-205AFC-T NSM-205AFT-T NSM-205AFC-T NS-206AFT-T NS-206AFC-T NSM-206AFT-T NSM-206AFC-T	Multi mode fiber cables: 50/125, 62.5/125 or 100/140 μm Distance: 2 km, (62.5/125 μm recommended) for full duplex Wavelength: 1300 or 1310 nm Min. TX Output: -20 dBm Max. TX Output: -14 dBm Max. RX Sensitivity: -32 dBm Min. RX Overload: -8 dBm Budget: 12 dBm		
Single-Mode	NS-205AFCS-T NSM-205AFCS-T NS-206AFCS-T NSM-206AFCS-T	Single-mode fiber cables: 8.3/125, 8.7/125, 9/125 or 10/125 μm Distance: 30 km, (9/125 μm recommended) for full duplex Wavelength: 1300 or 1310 nm Min. TX Output: -15 dBm Max. TX Output: -8 dBm Max. RX Sensitivity: -34 dBm Min. RX Overload: -5 dBm Budget: 19 dBm		
Single-Mode	NS-205AFCS-60T NSM-205AFCS-60T NS-206AFCS-60T NSM-206AFCS-60T	Single-mode fiber cables: 8.3/125, 8.7/125, 9/125 or 10/125 μm Distance: 60 km, (9/125 μm recommended) for full duplex Wavelength: 1300 or 1310 nm Min. TX Output: -5 dBm Max. TX Output: 0 dBm Max. RX Sensitivity: -35 dBm Min. RX Overload: -5 dBm Budget: 30 dBm		
Power Input				
Input Voltage Range	+12 V _{dc} ~ +48 V _{dc} (Redundant input)			
Power Consumption	0.2 A @ 24 V _{dc}	0.14 A @ 24 V _{dc}	0.2 A @ 24 V _{dc}	0.14 A @ 24 V _{dc}
Protection	Power reverse polarity protection			
+/-4 kV ESD Protection	Yes			
Connector	6-Pin Removable Terminal Block			
Mechanical				
Casing	Plastic (Flammability UL 94V-0)		Metal (IP30 Protection)	
Dimensions (W x L x H)	31 mm x 127 mm x 157 mm		25 mm x 133 mm x 168 mm	
Installation	DIN-Rail Mounting			
Environmental				
Operating Temperature	-30 °C ~ +75 °C			
Storage Temperature	-40 °C ~ +85 °C			
Ambient Relative Humidity	10% ~ 90% RH, non-condensing			