



System

Form Factor	2.5-inch Disk-Size SBC
CPU	NXP Cortex™-A9 i.MX 6Dual-Lite 1GHz
System Memory	1GB DDR3 on board
Data Memory	4GB eMMC on board
Display	1x 18/24-bit single LVDS, up to 1366 x 768 1x HDMI V1.4, up to 1080P30 at 60Hz
Video Codec	Encoder: MPEG-4 SP, H.264 BP, H.263, MJPEG BP Decoder: MPEG-4 ASP, H.264 HP, MPEG-2 MP, MJPEG BP
LAN	10/100/1000 Mbps
Touch	USB
Audio	2x 5-pin header, 1.0mm (1x line-in, 1x line-out)
RTC	IDT 1337AGDVG18
Watchdog	256 levels, 0~128 secs
Edge I/O	1x GbE (RJ45 connector) 1x USB Type-A, 1x USB OTG Mini-USB 1x HDMI 1x RS232/422/485 (D-SUB 9 male connector) 1x Micro SD socket (UHS-I SDR-104, max.104MB/s) 1x Reset button
Header, Expansion & LEDs	1x LVDS connector (Hirose DF13-20) 1x Backlight, 3.3V/1A, 5V/1A, 12/1A (jumper selection) 1x 4-pin wafer (for debug console port) 1x Audio pin header (Line-in and Line-out) 2x 2-wire UART (1x6 pin header, 1.0mm) 2x USB 2.0 (2*5 pin header 1.0mm) 1x M.2 Key-E (2230) w/ PCI-E, USB, SDIO, UART 8x GPIO (2*5 pin header 1.0mm) 2x Green LEDs (for Power On/Off, and Wireless status)
Dimensions	100mm x 72mm (3.94" x 2.83")
Power	12V DC-in by DC-jack

Features

- NXP Cortex™-A9, i.MX 6Dual-Lite 1GHz processor
- Supports HDMI and single LVDS interface
- Supports 1GB DDR3, 4GB eMMC and Micro SD socket for expansion
- Embedded I/O as COM, GPIO, USB, USB-OTG, audio and Ethernet
- M.2 Key-E (2230) for wireless connectivity
- OpenGL ES 2.0 for 3D BitBit for 2D and OpenVG1.1

Operating Temperature	-40°C ~85°C (-40°F ~ 185°F) with heatsink
Devices	WiFi/BT module (option)
Software Support	Yocto 2.1 (Kernel 4.1.15) Android 6.0.1
Relative Humidity	10%~90% (non-condensing)
Certification	CE/ FCC Class B

Ordering Information

IBR115	2.5" ARM-based SBC, NXP Cortex™-A9, i.MX 6Dual-Lite 1GHz, 1GB DDR, 4GB eMMC, Single LVDS, HDMI, RS-234/422/485, USB, M.2 Key E(2230)
Heatsink	HSIBR115-A
Cable	LCD403, Panel cable for 7" LCD404, Panel cable for 15" MT-76, Backlight for 7" and 15" panel PK1-135, GPIO PK1-133, COM port USB-81, USB OTG cable PK1-100A, Debug cable
RF module	WNFT-234ACN, WiFi/BT M.2 module
Display	AM-1024600ATMQW-A0H: - 7" Capacitive LVDS TFT LCD, 1024 x 600 M150GNN2 R1: - 15" Capacitive LVDS TFT LCD, 1024 x 768



Backplane Systems Technology

Backplane Systems Technology Pty Ltd
TEL 02 9457 6400
sales@backplane.com.au
www.backplane.com.au