

# VBOX-3611-4L

Intel Gen6 Core i7-6600U CPU with 4 x GbE LAN  
On-Board Computer

## Features

- Intel Core i7-6600U
- Wireless support LTE w/ Dual SIM Cards, WLAN, GPS Dead Reckoning, WiFi, BT (Optional)
- 9V - 48V DC Power Input
- Smarter Vehicle Power Ignition for Variety Vehicle
- Dual Hot Swappable SATA Storage, RAID 0, 1, 5
- 1 x CAN Bus 2.0B (Optional)
- E13 and EN50155 certified



Taiwan Patent No. M447854

Taiwan Patent No. M448011



Backplane  
Systems  
Technology

Backplane Systems  
Technology Pty Ltd

TEL 02 9457 6400  
sales@backplane.com.au  
www.backplane.com.au

Proudly Australian-Owned Since 1989



Delay Time



Power Ignition



Wide Range



Wireless



Battery Backup

System	
CPU	Intel Gen 6 Core i7-6600U 2.6GHz up to 3.4GHz Intel Gen 6 Core i5-6300U 2.4GHz up to 3.0GHz Intel Gen 6 Core i3-6100U 2.3GHz Intel Gen 6 Dual Core 3955U 2.0GHz
Memory	2 x DDR4 2133 MHz SO-DIMM up to 32GB
Chipset	Intel 6th Generation Core SoC Processor
LAN Chipset	Intel I210-AT Gb/s Ethernet Controllers Onboard Support PXE and WOL
Audio	Realtek ALC662 HD Codec Onboard
Watchdog	Watchdog Timer Support, Offer 1 – 255 Step
TPM	2.0
I/O	
Serial Port	4 x RS-232 (2 with RS-422/485 (Auto Direction Control))
USB Port	4 x USB 3.0 Ports
LAN	4 x RJ45 Ports (optional M12 connector) for GbE ( 1 port with iAMT)
Video Port	1 x DVI-I*, 1 x VGA and 1 x DP (support Triple Independent Display)
DIO Port	4 In and 4 Out
Audio	1 x Line-out and 1 x Mic-in (Line-in Optional)
SIM Card Socket	2 x SIM Card Sockets Supported Onboard with eject
Expansion Bus	3 x mini-PCIe cards, 1 x M.2 2230 A-E Key *Use only with Single Link DVI Cables.
Power Requirement	
Power Input	9V - 48V DC Power Input
Power Protection	Automatics Recovery Short Circuit Protection
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by BIOS and Software
Battery(UPS)	Internal Battery Kit for 10 Mins Operating (Optional) <b>Patent No. : M447854 - Build-in Battery</b>

Software	
Operating System	Win 10, Ubuntu 16.04 64bit
Storage	
Type	2 x 2.5" Drive Bay for SATA Type HDD/SSD RAID 0, 1, 5 1 x SATA DOM
Graphics	
Graphics	Intel® HD Graphics 520 DirectX Video Acceleration (DXVA) for Accelerating Video Processing - Full AVC/VC1/MPEG2 HW Decode Supports DirectX 11/10.1/10/9 and OpenGL 4.0
Resolution	Max Resolution (HDMI1.4) : 4096x2304@24Hz Max Resolution (DP) : 4096x2304@60Hz
Environmental	
Operating Temp.	-40°C ~ 70°C, ambient w/ 0.6m/s airflow
Storage Temp.	-40°C ~ 85°C
Relative Humidity	10% RH ~ 90% RH (non-condensing)
Vibration (random)	IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD
Vibration Operating	MIL-STD-810G, Method 514.6, Procedure I, Category 4
Shock	Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Certifications	CE, FCC Class A, E13, EN50155, EN45545-2 (R25) (The input Negative connects with chassis Ground)
Mechanical	
Construction	Aluminum Alloy
Mounting	Supports Both of Wall-mount/VESA-mount
Weight	2160 g (Barebone)
Dimensions	250 x 150 x 55 mm
Ordering Information	
Part Number	VBOX-3611-4L-i7
Description	Intel Gen6 Core i7-6600U CPU with 4 x GbE LAN On-Board Computer
State of Origin	Made in Taiwan