## Technology Pty Ltd

TEL 02 9457 6400 sales@backplane.com.au www.backplane.com.au

# ITMH100-EX

### Intel® Core™ i5-1135G7 CID2 M Series Box PC



#### **KEY FEATURES**

- Intel® Tiger Lake UP3 Core™ i5-1135G7
- Multi Video Output , HDMI/Display Port, Intel® Core™ i5 C1D2 Box
- Auto detection of the connected display, No settings necessary
- Quick & Easy Replaceable Hard Disk Design, No Tools required
- Support wide range 9-29V DC input
- Optional with Modular front Display as a Panel PC
- Expansion slot for PClex4
- Class 1, Division 2, ATEX Grade zone 2 and IECEx certified for hazardous area applications




#### **SPECIFICATIONS**

System Specification					
WLAN	Support (Optional)	ВТ	Support (Optional)		
<b>Expansion Port</b>	Modular Design for easy service in the field	Processor	Intel Core i5-1135G7 2.4GHz (up to 4.2GHz)		
Memory	2 x SO-DIMM, DDR4 3200 MHz, 4GB 8GB (Optional) 16GB (Optional) 32GB (Optional)	Storage	1 x M.2 2280 NVMe SSD, 128GB up to 512GB 1 x 2.5" Removable 256GB SSD up to 512GB (Optional)		
Ethernet controller	Intel® Ethernet Controller I211-AT + Intel® Ethernet Connection I219-LM	Operating System	n Windows 10 IoT Enterprise (64 bit) (Optional)		
Mechanical					
Dimension	276 x 207 x 60 mm	Mounting	VESA Mount		
Enclosure	Metal Housing	Cooling System	Fanless design		
Environment					
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	0°C to 50°C		
Storage Temperature	-10°C to 60°C				
Certification					
Certification	CE, FCC Class 1, Division 2, Group A, B, C, D, T5 IECEx Ex ec ic IIC T5 Gc Compliance with ATEX grade zone 2				
IO Ports					
Power Input	1 x 9~29V DC, 3-Pin Terminal Block	USB Port	4 x USB 3.2 Gen.1 (Type-A)		
Serial Port	2 x RS232/422/485 (Default RS232) 1 x RS232	Video	1 x DP1.4 1 x HDMI 2.0 (Optional)		
Audio	1 x Audio Combo Connector (Mic in / Line Out)	Expansion Port	1 x mPCle slot 1 x PCle x16 slot (x4 signal)(module max size:180x121mm) 1 x M.2 2230 Key E slot for WiFi 1 x M.2 2280 Key M slot for NVMe SSD Swappable 2.5" HDD/SSD Bay Slot		
LAN	2 x Giga LAN RJ45 Connector	Indicator	1 x LED Indicator for storage		

Control				
Button	1 x Power Button with LED Indicator 1 x Reset Button			
Accessory				
Accessory	100~240V AC to DC Adapter Power Cord Open Wire Cable with terminal block connector VESA screws			
Power				
Power Rating	9V~29V DC with protection fuse	Adapter	12V 84W	

#### **DIMENSIONS** UNIT:MM



## NOTE

- 1. This is a simplified drawing and some components are not marked in detail.
- 2. Please contact our sales representative if you need further product information.
- 3. All specifications are subject to change without prior notice.
- 4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.