



Datasheet

U.2 SSD 4TG2-P series

- PCIe Gen. 4x4, NVMe 1.4
- Excellent data transfer speed
- Heat-spreading design
- LDPC ECC engine supported.
- End-to-end Data Path Protection
- High capacity & ultra-speed



Introduction


Innodisk U.2 SSD 4TG2-P is an NVM Express SSD designed as PCIe SFF-8639 module with PCIe interface and 3D TLC NAND Flash. U.2 SSD 4TG2-P supports PCIe Gen 4x4, and it is compliant with NVMe 1.4 providing excellent performance. With sophisticated error detection and correction (ECC) functions, the module can ensure full End-to-end Data Path Protection that secures the data transmission between host system and NAND Flash.

Innodisk U.2 SSD 4TG2-P provides ultra-speed and high IOPS and offers maximum capacity up to 8TB, making the SSD optimal for server and heavy data workload applications.

U.2 SSD

4TG2-P series

Diagram



Contact us for more information about the U.2 SSD 4TG2-P.

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2022 Innodisk Corporation.
All right reserved. Specifications are subject to change without prior notice.

20221110

Interface	PCIe Gen. 4 x4
Flash Type	3D TLC
P/E cycle	3,000
Capacity	512GB~8TB
Max. Channels	8
Sequential R/W (MB/sec, max.)	7150/6150
Max. Power Consumption	13.5W
Thermal Sensor	√
External DRAM buffer	√
H/W Write Protect	NA
iCell	NA
Dimension (WxLxH)	100.0 X 69.85 X 6.9 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Working Temperature: ST 0°C ~ +70°C, ; WT -40°C ~ +85°C Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

Ordering Information

Operation Temp.	512GB	1TB	2TB	4TB	8TB
Standard Grade (0°C ~ +70°C)	DGEU2-C12DP1KCAEF	DGEU2-01TDP1KCAEF	DGEU2-02TDP1KCAEF	DGEU2-04TDP1KCAEF	DGEU2-08TDP1KCAEF
Industrial Grade (-40°C ~ +85°C)	DGEU2-C12DP1KWAEF	DGEU2-01TDP1KWAEF	DGEU2-02TDP1KWAEF	DGEU2-04TDP1KWAEF	DGEU2-08TDP1KWAEF



Backplane Systems
Technology Pty Ltd

Backplane
Systems
Technology

TEL 02 9457 6400
sales@backplane.com.au
www.backplane.com.au

Proudly Australian-Owned Since 1989